

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17-5-2018 Revision date: 15-3-2023
Supersedes version of: 27-9-2022 Version: 1.8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : FIREZONE CLASSIC GEAR OIL GL-4 80W90
Product code : P40221
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Transmission oil
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

EG Group Benelux
Bagven Park 5
4838 EH Breda
Netherlands
+31 76 523 9200

1.4. Emergency telephone number

| Country | Organisation/Company | Address | Emergency number | Comment |
|----------------|--|---|------------------|---|
| Netherlands | National Poison Information Center | Huispostnummer B.00.118 Postbus 85500 3508 GA Utrecht | +31 88 755 80 00 | Only intended to warn professionals in the event of acute poisoning |
| United Kingdom | National Poisons Information Service (Cardiff Centre) University Hospital Llandough | Penlan Road CF64 2XX Cardiff | 0344 892 0111 | Only for healthcare professionals |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP) :

P273 - Avoid release to the environment.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Highly refined mineral oils and additives.

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|--|-----------|--|
| Polysulfides, di-tert-Bu | CAS-No.: 68937-96-2 EC-No.: 956-717-2 REACH-no: 01-2119540515-43 | 0,3 – 2,5 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| C16-18-(even numbered, saturated and unsaturated)-alkylamines | CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19 | < 0,1 | Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10) |

Specific concentration limits:

| Name | Product identifier | Specific concentration limits |
|---|--|--------------------------------------|
| C16-18-(even numbered, saturated and unsaturated)-alkylamines | CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19 | (10 \leq C < 100) STOT RE 2, H373 |

Comments

: The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Storage temperature : 0 – 40 °C

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| FIREZONE CLASSIC GEAR OIL GL-4 80W90 | |
|---|---|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended | 5 mg/m ³ - ACGIH TLV (inhalable fraction). |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

| Eye protection | | | |
|----------------|----------------------|-----------------|----------|
| Type | Field of application | Characteristics | Standard |
| Safety glasses | Droplet | clear | EN 166 |

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Hand protection | | | | | |
|-----------------|----------------------|-------------------|----------------|-------------|------------|
| Type | Material | Permeation | Thickness (mm) | Penetration | Standard |
| Reusable gloves | Nitrile rubber (NBR) | 6 (> 480 minutes) | ≥0.35 | | EN ISO 374 |

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Colour | : brown. |
| Odour | : characteristic. |
| Odour threshold | : Not available |
| Melting point | : Not applicable |
| Freezing point | : -27 °C - ASTM D5950 (pour point) |
| Boiling point | : Not available |
| Flammability | : Not applicable |
| Explosive properties | : Presents no particular fire or explosion hazard. |
| Explosive limits | : Not available |
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : 214 °C - ASTM D92 (COC) |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : Not available |
| Viscosity, kinematic | : 150,5 mm²/s (40 °C) - ASTM D7042 |
| Solubility | : Water: Insoluble / Slightly miscible |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : Not available |
| Vapour pressure at 50°C | : Not available |
| Density | : 0,893 kg/l (15 °C) - ASTM D4052 |
| Relative density | : Not available |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 %

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No decomposition if stored normally.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Polysulfides, di-tert-Bu (68937-96-2)

| | |
|-----------------|--------------|
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rat | > 2000 mg/kg |

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|-----------------|--|
| LD50 oral rat | 1689 mg/kg |
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |

Skin corrosion/irritation : Not classified

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----|-------------------|
| pH | 11,7 Temp.: 20 °C |
|----|-------------------|

Serious eye damage/irritation : Not classified

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----|-------------------|
| pH | 11,7 Temp.: 20 °C |
|----|-------------------|

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

STOT-repeated exposure : Not classified

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|--|--|
| NOAEL (subchronic, oral, animal/male, 90 days) | 100 mg/kg bodyweight (OECD 422 method) |
| STOT-repeated exposure | May cause damage to organs (digestive tract, liver) through prolonged or repeated exposure (oral). |

Aspiration hazard : Not classified

FIREZONE CLASSIC GEAR OIL GL-4 80W90

| | |
|----------------------|---|
| Viscosity, kinematic | 150,5 mm ² /s (40 °C) - ASTM D7042 |
|----------------------|---|

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----------------------|--------------------------|
| Viscosity, kinematic | 5,245 mm ² /s |
|----------------------|--------------------------|

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Not rapidly degradable

FIREZONE CLASSIC GEAR OIL GL-4 80W90

| | |
|----------------------|------------|
| LC50 - Fish [1] | > 100 mg/l |
| EC50 - Crustacea [1] | > 100 mg/l |
| ErC50 algae | 24,8 mg/l |

Polysulfides, di-tert-Bu (68937-96-2)

| | |
|----------------------|--|
| EC50 - Crustacea [1] | 0,24 mg/l |
| EC50 72h - Algae [1] | 0,838 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| ErC50 algae | 0,838 mg/l |

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----------------------|--|
| LC50 - Fish [1] | 0,06 mg/l |
| EC50 - Crustacea [1] | 0,011 mg/l |
| EC50 72h - Algae [1] | 0,46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| EC50 72h - Algae [2] | 0,38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| ErC50 algae | 0,04 mg/l |
| LOEC (chronic) | 0,032 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 0,013 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic algae | 0,013 mg/l |

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

Polysulfides, di-tert-Bu (68937-96-2)

| | |
|----------------|--------------------|
| Biodegradation | 13 % (Sturm, 28 d) |
|----------------|--------------------|

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----------------|------|
| Biodegradation | 66 % |
|----------------|------|

12.3. Bioaccumulative potential

Polysulfides, di-tert-Bu (68937-96-2)

| | |
|---|--------------------------------------|
| Partition coefficient n-octanol/water (Log Kow) | 6 (Octanol/water coefficient, 0,1 d) |
|---|--------------------------------------|

C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

| | |
|----------------|-----------------------------|
| BCF - Fish [1] | 500 mg/l (calculated value) |
|----------------|-----------------------------|

| | |
|---|-------------|
| Partition coefficient n-octanol/water (Log Kow) | 4,33 (25°C) |
|---|-------------|

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|--|
| Waste treatment methods | : Do not allow into drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Product/Packaging disposal recommendations | : Dispose in a safe manner in accordance with local/national regulations. |
| European List of Waste (LoW) code | : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils |

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|---|---------------|---------------|---------------|---------------|
| 14.1. UN number or ID number | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.2. UN proper shipping name | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.3. Transport hazard class(es) | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.4. Packing group | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| ADR | IMDG | IATA | ADN | RID |
|--|---------------|---------------|---------------|---------------|
| 14.5. Environmental hazards | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

| EU restriction list (REACH Annex XVII) | | |
|--|--|---|
| Reference code | Applicable on | Entry title or description |
| 3(c) | FIREZONE CLASSIC GEAR OIL GL-4 80W90 | Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1 |

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 0 %

Biocide Regulation (528/2012)

Child-resistant fastening : Not applicable

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tactile warning :Not applicable

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

| Indication of changes | | | |
|-----------------------|--------------------------------|----------|----------|
| Section | Changed item | Change | Comments |
| | Revision date | Modified | |
| | Supersedes | Modified | |
| 2.2 | Precautionary statements (CLP) | Modified | |

| Abbreviations and acronyms: | |
|-----------------------------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |

FIREZONE CLASSIC GEAR OIL GL-4 80W90

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

| Abbreviations and acronyms: | |
|-----------------------------|--|
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment – Acute Hazard, Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment – Chronic Hazard, Category 1 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Skin Corr. 1 | Skin corrosion/irritation, Category 1 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.