INSTALLATION INSTRUCTION FOR ROOF RACK

Note: Please read this instruction carefully prior to installation.

Please refer to your fitting instruction to ensure that the Roof Rack System is installed in the correct location

Check the content of kit before commencing fitment and report any discrepancies.

Place these instruction in the vehicle's glove box after installation is complete.

A. Locate all parts lay then on a flat surface.

Including parts are as below:









A. End Assembly×2

B. Wood Slat×10

C. Guardrail×2

D. Center Cross Tube $\times 1$





0





E. Hook Clampsx2

F. Fasteners


Screw*20 Screw*6

G. Washers × 40

H. Nuts×28


I. Plastic protectors

- B. Follow the Installation Steps.
- Install two Guardrail, Center Cross Tube into the End Assembly. Screw with a washer from the top and then attach another washer and a nut to screw from the bottom. Leave fasteners only finger tight at this time.





- 2. Install the other End Assembly into the other end of the Guardrail, Center Cross Tube.
- 3. Insert one end of the wood slates with arch facing up (ends of channels touching work surface) into the Cross Channels side to side continue for all slats. Screw with a washer from the top and then attach another washer and a nut to screw from the bottom. Leave fasteners only finger tight.





4. Carefully align all of the tabs and shafts with corresponding parts and fasten same as opposite end. Install clamps on end assembly by unscrewing wing nut and sliding threaded stud up through tube on center leg, reinstall wing nut but don't tighten. Install plastic protectors on rack feet.



5. Measure side to side across the front and rear feet the narrower end faces the front of the car. Get someone to help you lay the rack onto the roof of the car. The feet of the rack should sit down into the rain gutter. Once positioned properly, hook clamps under rain gutter in door opening (with door open) and tighten wing nuts.

